



GLOBAL 5000



Providing the widest and most spacious cabin among super-large business jets, the powerful, versatile Bombardier' Global 5000' offers an impressive combination of speed and performance plus superior cabin productivity. With its extraordinary short-field performance and transcontinental range, this super-large jet can carry world leaders to more places faster than any other in its class. All in the luxury of corporate aviation's most comfortable and 'business connected' cabin.

- Faster and more short-field capable than any other in its class
- · Cabin that leads all others in space, luxury and productivity
- Innovative flight deck environment combines cutting-edge technology and advanced design



GENERAL

Capacity

Crew: 2-3


Passengers: 8-17 (business/high-density interior)

Engines

Rolls-Royce Deutschland BR710A2-20 turbofans Thrust: 14,750 lb (65.6 kN) Flat rated to: ISA + 20°C (95°F)

Avionics and Cabin Communication

- Rockwell Collins Pro Line Fusion avionics suite
- Four 15.1-inch (38.4 cm) Liquid Crystal Display (LCD) screens
- Head-Up Display System (HUD), 3rd generation Enhanced Vision System (EVS) and Synthetic Vision System (SVS)
- Onboard Maintenance System (OMS)
- Advanced diagnostic and troubleshooting tool integrated with most aircraft systems: available on Multi-Function Display or for download onto a portable computer.
- Available both on the ground and in flight, OMS minimizes troubleshooting workload and reduces aircraft downtime
- Datalink, SATCOM: triple channel Inmarsat, single channel Iridium
- Ethernet-based Cabin Electronic System with on-board Local Area Network
- Single channel high-speed data, printer/fax



Bombardier Aerospace, Business Aircraft, 400 Côte-Vertu Road West, Dorval, Québec, Canada H4S 1Y9 In North America call 800-268-0030 • Elsewhere call 514-855-7698 • www.businessaircraft.bombardier.com

Performance is based on maximum takeoff/landing weight, sea level, standard day (ISA) conditions, unless otherwise noted. All data in this document is approximate, for discussion purposes only and may be subject to certain conditions. All internai dimensions are based on an aircraft without a completed interior. This document does not constitute an offer, commitment, representation or warranty of any kind. All data is subject to change without prior notice. The interior images shown are for information purposes only and may represent some optional configurations. The final configuration and performance of the aircraft shall be as per the contractually aread upon purchase agreement.

©2010 Bombardier Inc. All rights reserved. *Registered Trademark(s) or Trademark(s) of Bombardier Inc. or its subsidiaries. Printed in Canada (10/10).

PERFORMANCE

High-speed 0.89

Airfield Performance

5,540 ft (1,689 m)

2,670 ft (814 m)

Operating Altitude

51,000 ft (15,545 m)

Noise Level (EPNdB)

Flyover: 80.1

Lateral: 89.7

Approach: 88.2

5,200 NM

(Theoretical range with NBAA IFR Reserves, ISA,

weather, selected options and other factors.)

Mach

8 pax/3 crew. Actual range will be affected by speed,

cruise speed 0.85 488 562 904

Takeoff distance (SL, ISA, MTOW):

Landing distance (SL, ISA, MLW):

Maximum operating altitude:

Relative cabin pressure altitude

at 45,000 ft (13,716 m): 4,500 ft (1,371 m)

513

Range

Speed

Typical

At M 0.85:

_

9,630 km

kt mph km/h

590 950

DIMENSIONS Exterior

Length: 96.8 ft (29.5 m) Wingspan: 94 ft (28.6 m) Wing area: 1,022 ft² (94.9 m²) (basic) Height overall: 25.5 ft (7.7 m)

Interior

Cabin length: 45.66 ft (13.92 m) (from start of forward lavatory to end of pressurized compartment)

Cabin width: 8.17 ft (2.49 m)

Cabin width: 6.92 ft (2.11 m)

Cabin height: 6.25 ft (1.91 m)

Floor area: 317 ft² (29.4 m²) (excluding cockpit)

Cabin volume: 2,022 ft³ (57.26 m³) (from start of forward lavatory to end of pressurized compartment)

Weights

A. Maximum ramp weight: 92,750 lb (42,071 kg)

- B. Maximum takeoff weight: 92,500 lb (41,957 kg)
- C. Maximum landing weight: 78,600 lb (35,652 kg)
- D. Maximum zero fuel weight: 56,000 lb (25,401 kg)
- E. Typical basic operating weight: 50,840 lb (23,061 kg)
- F. Maximum fuel weight: 39,250 lb (17,804 kg)

Maximum payload (D-E): 5,160 lb (2,341 kg)

Payload - maximum fuel (A-E-F): 2,660 lb (1,207 kg)

Fuel for executive mission (8 pax/3 crew): 38,800 lb (17,599 kg)

BOMBARDIER